

For a Free Quote:

Web: EnergyPal.com/solar

Call: 1-800-990-3725


Email: contact@energypal.com

EnergyPal

Solar Panel Guide Specification Data Sheet

**Aditya Kiran
Poly 10-150W
100W**

Also available on the web at
EnergyPal.com/aditya-kiran-solar-panels/100w



AK SOLAR PANEL

World class solar photovoltaic modules for specialty applications

Rugged & durable design enabling easy installation & long life

Customized models available to meet specific applications

Peace of mind guaranteed with aditya kiran solar panel

Leading edge-equipment plus world class processes from BP Solar

High quality modules manufactured by aditya kiran in india for over 20 years



PRODUCT FEATURES


- High power output using high efficiency cells and ultra-clear solar glass
- UV resistant, weather-proof junction boxes with bypass diodes
- Torsion and corrosion resistance with anodized screw type aluminium frame
- Higher impact resistance using scratch resistant toughened solar glass

APPLICATIONS

- Lighting: lanterns, indoor and street
- Telecommunication and radio relay stations
- Stand alone systems / telemetry systems
- Defence and offshore requirements
- Signage and outdoor media
- Mobile chargers / outdoor activities

SPECIFICATIONS

- Multiple configurations (36, 48 and 72 cells)
- Multiple wattages (10 to 255Wp)
- Mono and multi-crystalline cells (125mm and 156mm)
- IV curve and specifications available for all products



Modules in the Gold series

Gold

	10	40	80	100	150
--	----	----	----	-----	-----

Electrical parameters at standard test conditions (STC)*

	10	40	80	100	150
Nominal power output (W)	10	40	80	100	150
Power tolerance (%)	-5 ~ +5	-5 ~ +5	-5 ~ +5	-5 ~ +5	-5 ~ +5
Voltage at P _{MAX} V _{MPP} (V)	17.6	17.8	17.6	17.6	18.1
Current at P _{MAX} I _{MPP} (A)	0.55	2.22	4.55	5.68	8.27
Open-circuit voltage V _{oc} (V)	21.8	21.8	21.8	21.8	22.5
Short-circuit current I _{sc} (A)	0.60	2.45	4.90	6.15	8.68

Module general characteristics

Number of cells	36	36	36	36	36
Length (mm)	460	651	1205	1202	1504
Width (mm)	288	538	538	661	661
Thickness (mm)	17	38.5	38.5	38.5	38.5
Weight (kg)	1.8	4	7.5	9	12
Frame material	Silver anodized aluminium				
Superstrate	3.2 mm glass				
Substrate	PET				
Encapsulant	EVA				

Environment and operating conditions

Operating temperature range (°C)	-40 and +85
----------------------------------	-------------

Warranty

Product warranty (years)	5
Power output warranty (years)	10 (90% of rated power output) 25 (80% of rated power output)

Wide range of Ak Gold series modules include the following:
10, 20, 37, 40, 50, 55, 60, 70, 75, 80, 90, 100, 125, 130, 150,
190, 230, and 255 Wp.

Applications

Stand alone systems for homes with no grid connectivity

Street lighting and community lighting

Lighting billboards and outdoor media

Offshore installations and hazardous locations

Portable mobile phone charger

Power packs for remote telecom sites & telemetry stations

ADITYAKIRAN

Manufacture of Solar Panels & Supplier of LED lights & Solar Projects

Work: 1413A, Gidc Waghodia-391760 Vadodara, Gujarat-india | **Mob.:** 09879746910

Email: info@adityakiran.co.in | **web:** www.adityakiran.co.in