

For a Free Quote:

Web: EnergyPal.com/solar

Call: 1-800-990-3725

Email: contact@energypal.com

EnergyPal

Solar Panel Guide Specification Data Sheet

**Aditi Solar Private Limited
Aditi 12V - 55WP
12V - 55WP**

Also available on the web at
EnergyPal.com/aditi-solar-private-limited-solar-panels/12v-55wp



SOLAR PHOTOVOLTAIC MODULES

Aditi's Photovoltaic Modules

- ★ High efficiency, Mono or Multi crystalline solar cells with high transmission and textured glass delivering a module series efficiency of up to 14.3%, minimizing installation costs and maximizing the kWh output of your system per unit area.
- ★ High quality, low iron, high transmissivity, tempered and toughened glass to ensure high light absorption.
- ★ Tin Copper interconnect increases Solderability and Conductivity. This also results in maximum output efficiency from the Module.
- ★ Premium quality encapsulation material ensuring high quality lamination leading to better performance.
- ★ Polyster tedlar used as a back sheet prevents from moisture and mechanical damage.
- ★ Weather resistant frame - seal helps preventing water seepage and protects the system from humidity.
- ★ Anodized Aluminum frame gives the system strong, corrosion-free structural support.
- ★ Produced in an ISO 9001:2008 & 14001:2004 certified production facilities.
- ★ Certifications: IEC 61215, IEC 61730-1&2, IEC 61701.
- ★ Warranty,
 - a) 90% of the rated power is guaranteed for a period of 10 years.
 - b) 80% of the rated power is guaranteed for a period of 25 years.




Model No: ADT 1255

Electrical Specifications:

| | |
|---|-------------------|
| Product Description | 12V - 55WP |
| Rated POWER Pmax - [W] | 55.00 |
| Rated Voltage Vmax - [V] | 17.50 |
| Rated Current I_{max} - [A] | 3.14 |
| Open Circuit Voltage V_{oc} - [V] | 21.50 |
| Short Circuit Current I_{sc} - [A] | 3.36 |
| Module Efficiency η - [%] | 13.90 |
| Tolerance | ± 3% |

Standard Test Conditions: Irradiance 1000 W/ m², Module temperature 25°C, Spectrum AM 1.5

Module IV-Curve:



Temperature Coefficients


| | |
|-------------------------------|-------------------|
| Voltage V_{oc} | : -0.33%/K |
| Current I_{sc} | : +0.06%/K |
| Power P_{max} | : -0.40%/K |

| | |
|-------------------------------------|-------------------------|
| Maximum system voltage | : 1000 V DC |
| Operating Module Temperature | : -40°C to +85°C |
| NOCT | : 47°C ± 2°C |

Certifications



Module Drawing & Mounting details:



Mechanical Specifications:

| | |
|--------------------|--------------|
| Length [mm] | 595 ± 2 |
| Width [mm] | 665 ± 2 |
| Thickness [mm] | 34 |
| X [mm] | 355 ± 2 |
| Y [mm] | 620 ± 2 |
| Mounting hole | 10X7 mm slot |
| Earth hole | 5mm dia |
| Aprox. weight [Kg] | 4.50 |
| No. of cells | 36 / 72 |

Other Characteristics:

| | |
|--------------------|---|
| Cell type | Mono / Multi Crystalline |
| Front Glass | Toughened Textured Glass |
| Glass thickness | 3.2 mm |
| Cell Encapsulation | EVA (Ethylene Vinyl Acetate) |
| Back sheet | Poly vinyl Fluoride |
| Frame | Anodized, Extruded Aluminum frame |
| Junction Box | Nylon / ABS moulded 3 rail junction box |

Due to continuous upgradation of products, specifications mentioned are subject to change without prior notice.



Plot No: 17, ALEAP Indust. Estate, Gajula Ramaram, Qutbullapur (M), R.R.Dist., HYDERABAD 500090, ANDHRA PRADESH – INDIA TEL:+91-40-2004 0285 MOB: +91-8978854777 / 555
WEBSITE: www.aditisolar.in, EMAIL: marketing@aditisolar.in, spvprojects@aditisolar.in