

For a Free Quote:

Web: EnergyPal.com/solar

Call: 1-800-990-3725

Email: contact@energypal.com

EnergyPal

Solar Panel Guide Specification Data Sheet

Calyxo GmbH

CX1/3

CX1 82/3

Also available on the web at
EnergyPal.com/calyxo-gmbh-solar-panels/cx1-82-3

Length x Width	1200 mm x 600 mm
Thickness	6.9 mm (21.0 including junction box)
Weight	12.0 kg
Front Cover	3.2 mm glass
Back Cover	3.2 mm glass
Cell Type	Cadmium telluride [CdTe]
Frame	none
Junction Box	Protection Class IP65
By-Pass Diode	none
Cable Type	Solar cable 2.5mm ²
Cable Length	650 mm (+Cable), 850 mm (-Cable)
Connector	Multicontact MC 4 optional MC3

TS Solar GmbH
 OT Thalheim, Sonnenallee 1a
 06766 Bitterfeld-Wolfen, Germany

TEL +49 (0)3494 368 980-0
 FAX +49 (0)3494 368 980-111

EMAIL service@calyxo.com
 WEB www.calyxo.com

Note: Installation instructions must be followed. See the instruction and operating manual or contact the technical service for further information on approved installation and use of the product. Specifications subject to technical changes. Printed on environment-friendly paper. © TS Solar GmbH EU/ENG; CX3 /3 Feb. 2019



ELECTRICAL CHARACTERISTICS

POWER CLASS			CX1	CX1	CX1	CX1	CX1
			75/3	77/3	80/3	82/3	85/3
Nominal Power [+10% / -5%]	P_{MPP}	[W]	75.0	77.5	80.0	82.5	85.0
Current at max. Power	I_{MPP}	[A]	1.29	1.30	1.32	1.33	1.35
Voltage at max. Power	V_{MPP}	[V]	58.3	59.7	61.0	62.6	63.8
Short Circuit Current	I_{SC}	[A]	1.50	1.53	1.54	1.56	1.57
Open Circuit Voltage	V_{OC}	[V]	87.8	88.3	88.9	90.0	91.0

Performance at normal operating cell temperature (NOCT: 800 W/m², 45 ±2°C, AM 1.5 Spectrum)

POWER CLASS			CX1	CX1	CX1	CX1	CX1
			75/3	77/3	80/3	82/3	85/3
Nominal Power	P_{MPP}	[W]	57.6	59.5	61.4	63.4	65.3
Current at max. Power	I_{MPP}	[A]	1.04	1.05	1.06	1.07	1.09
Voltage at max. Power	V_{MPP}	[V]	55.8	57.2	58.5	59.9	61.1
Short Circuit Current	I_{SC}	[A]	1.21	1.23	1.24	1.25	1.26
Open Circuit Voltage	V_{OC}	[V]	84.1	84.6	85.2	86.3	87.2

Performance at low irradiance

The typical relative change in module efficiency at an irradiance of 200W/m² in relation to 1000W/m² (both at 25°C and AM 1.5 spectrum) on request.

Temperature coefficients (at 1000W/m², AM 1.5 Spectrum)

Temperature I_{SC}	α	[%/K]	+ 0.03
Temperature V_{OC}	β	[%/K]	- 0.21
Temperature P_{MPP}	γ	[%/K]	- 0.20

Properties for system design (IEC)

Maximum System Voltage	V_{SYS}	[V]	1000
Maximum Reverse Current	I_R	[A]	2.0
Wind / Snow Load	p	[Pa]	2400
Safety Class			II
Fire Rating			C

The power classes are defined by sorting of power classes (+2.5W/0W) according to measured PMPP under STC. IMPP, VMPP, ISC, VOC are within ±10% of the indicated values under STC. Valid indoor measurement of STC performance is obtained by pretreating the module before measurement. For more information PAS-11-05-0203-EN.