

For a Free Quote:

Web: EnergyPal.com/solar

Call: 1-800-990-3725

Email: contact@energypal.com


EnergyPal

Solar Panel Guide Specification Data Sheet

**Eco Delta Power Co., Ltd.
ECO - 320-340M-60DHC-DGDF
ECO-330M-60DHC-DGDF**

Also available on the web at
EnergyPal.com/eco-delta-power-co-ltd-solar-panels/eco-330m-60dhc-dgdf

ECO DELTA High Efficiency 5BB Mono Big Cell Half-cut Double-glass-bifacial PV Module ECO-320-340M-60DHC-DGDF



Higher Module Efficiency

Brings 0-+3W Power gain due to half-cut production system



INNOVATIONAL HALF-CELL TECHNOLOGY

Improves the module output, decreases the risk of micro-crack, enhances the module reliability.



INNOVATIVE PERC CELL TECHNOLOGY

Excellent cell efficiency and output.



REDUCE SHADOW LOSS

Effectively reduces the effect of shadow on the module surface.



REDUCE INTERNAL MISMATCH LOSS

Reduces mismatch loss and improves output.



PASSED HAIL TEST


Certified to hail resistance: ice ball size (d=45mm) and ice ball velocity (v=30.7m/s).



PID RESISTANCE

Excellent PID resistance at 96 hours (@85°C/85%) test, and also can be improved to meet higher standards for the particularly harsh environment

LINEAR PERFORMANCE WARRANTY



QUALITY WARRANTY

Eco Delta guarantees that defects will not appear in materials and workmanship defined by IEC61215 or IEC61730 under normal installation, use and maintenance as specified in Eco Delta's installation manual for 12 years from the warranty starting date.

ISO9001
ISO14001
OHSAS18001



About Eco Delta

Eco Delta Power Co.,Ltd specializes in research, development, production, and sales of solar PV products as well as provision of related services and provides customers around the world with high-quality PV products.

www.ecodeltapower.com

ECO DELTA High Efficiency 5BB Mono Big Cell Half-cut Double-glass-bifacial PV Module



ECO-320-340M-60DHC-DGDF

ELECTRICAL DATA @ STC		ECO-320M-60 DHC-DGDF	ECO-325M-60 DHC-DGDF	ECO-330M-60 DHC-DGDF	ECO-335M-60 DHC-DGDF	ECO-340M-60 DHC-DGDF
Peak Power(Pmax)	(W)	320	325	330	335	340
Maximum Power Voltage (Vmp)	(V)	34.30	34.50	34.70	34.90	35.10
Maximum Power Current(Imp)	(A)	9.33	9.43	9.52	9.60	9.69
Open-circuit Voltage (Voc)	(V)	40.70	40.90	41.10	41.30	41.50
Short-circuit Current(Isc)	(A)	9.84	9.93	10.02	10.10	10.18
Module Efficiency	(%)	18.60	18.75	19.00	19.31	19.61
Operating Temperature		-40°C~+85°C				
Maximum System Voltage		<input type="checkbox"/> 1000V <input type="checkbox"/> 1500V				
Maximum Series Fuse Rating		15A				
Power Tolerance		0~+3%				

*STC (Standard Test Condition): Irradiance 1000W/ m², Module Temperature 25°C, AM 1.5

DIFFERENT BACKSIDE POWER GAINS (320W)	10%	15%	20%	25%	
Peak Power(Pmax)	(W)	352	368	384	400
MPP Voltage (Vmp)	(V)	34.30	34.30	34.30	34.30
MPP Current(Imp)	(A)	10.27	10.73	11.20	11.67
Open Circuit Voltage (Voc)	(V)	40.70	40.70	40.70	40.70
Short Circuit Current(Isc)	(A)	10.83	11.32	11.81	12.31

*STC (Standard Test Condition): Irradiance 1000W/ m², Module Temperature 25°C, AM 1.5

TEMPERATURE CHARACTERISTICS

Temperature coefficient of Pmax	-0.38%
Temperature coefficient of Voc	-0.31%
Temperature coefficient of Isc	0.05%
NMOT	41±3°C

MECHANICAL DATA

Cell Type	Mono-Crystalline, 158.75*79.38mm
Cell Arrangement	120pcs (2(6*10))
Dimension (L*W*H)	1720*1008*30mm
Weight	22.5kg
Front Cover	2.5mm Tempered Glass
Frame	Anodized Aluminium Alloy
Junction Box	IP67, 3 Bypass Diodes
Cable Type	4mm ²
Length of Cable	1160mm
Connector	PV Connector

OPTIONAL


Frame	<input type="checkbox"/> Black
Backsheet	<input type="checkbox"/> Black
Connector	<input type="checkbox"/> Original MC4
Cable	<input type="checkbox"/> 300mm <input type="checkbox"/> 1160mm
Module Size	<input type="checkbox"/> Customized

PACKING MANNER

Packing Type	40'HQ
Piece/Pallet	30
Piece/Container	780

*The specification and key features described in this datasheet may deviate slightly and are not guaranteed. Due to ongoing innovation, R&D enhancement, ECO DELTA POWER CO., LTD Reserves the right to make any adjustment to the information described herein at any time without notice. Please always obtain the most recent version of the datasheet which shall be duly incorporated into the binding contract made by the parties governing all transactions related to the purchase and sale of the products described herein.

Current-Voltage Curve under different irradiance



Current-Voltage Curve under different working temperatures

