

For a Free Quote:

Web: EnergyPal.com/solar

Call: 1-800-990-3725

Email: contact@energypal.com

EnergyPal

Solar Panel Guide Specification Data Sheet

Eco Delta Power Co., Ltd.

ECO - 355-370M-72DG

ECO-365M-72DG

Also available on the web at
EnergyPal.com/eco-delta-power-co-ltd-solar-panels/eco-365m-72dg

ECO DELTA 5BB Monocrystalline Double-glass PV Module

ECO-355-370M-72DG



Higher Module Efficiency

Brings 0-+3W positive tolerance on label rating power provides higher Kwh



INNOVATIONAL 5-BUSBAR CELLS

Reduces the cell series resistance and internal stress, decreases the risk of micro-crack and improves the module output.



INNOVATIVE PERC CELL TECHNOLOGY

Excellent cell efficiency and output.



REDUCE SHADOW LOSS

Effectively reduces the effect of shadow on the module surface.



REDUCE INTERNAL MISMATCH LOSS

Reduces mismatch loss and improves output.




PASSED HAIL TEST

Certified to hail resistance: ice ball size (d=45mm) and ice ball velocity (v=30.7m/s).




PID RESISTANCE

Excellent PID resistance at 96 hours (@85°C/85%) test, and also can be improved to meet higher standards for the particularly harsh environment



LINEAR PERFORMANCE WARRANTY



QUALITY WARRANTY

Eco Delta guarantees that defects will not appear in materials and workmanship defined by IEC61215 or IEC61730 under normal installation, use and maintenance as specified in Eco Delta's installation manual for 12 years from the warranty starting date.

ISO9001
ISO14001
OHSAS18001



About Eco Delta

Eco Delta Power Co.,Ltd specializes in research, development, production, and sales of solar PV products as well as provision of related services and provides customers around the world with high-quality PV products.

www.ecodeltapower.com

ECO DELTA 5BB Monocrystalline Double-glass PV Module


ECO-355-370M-72DG



ELECTRICAL DATA @ STC		ECO-355M-72DG	ECO-360M-72DG	ECO-365M-72DG	ECO-370M-72DG
Peak Power(Pmax)	(W)	355	360	365	370
Maximum Power Voltage (Vmp)	(V)	39.10	39.30	39.50	39.70
Maximum Power Current(Imp)	(A)	9.08	9.16	9.24	9.32
Open-circuit Voltage (Voc)	(V)	47.70	47.90	48.10	48.30
Short-circuit Current(Isc)	(A)	9.40	9.48	9.57	9.67
Module Efficiency	(%)	18.20	18.50	18.70	19.00
Operating Temperature		-40°C~+85°C			
Maximum System Voltage		<input type="checkbox"/> 1000V <input type="checkbox"/> 1500V			
Maximum Series Fuse Rating		15A			
Power Tolerance		0~+3%			

*STC (Standard Test Condition): Irradiance 1000W/ m², Module Temperature 25°C, AM 1.5


Current-Voltage Curve under different irradiance



ELECTRICAL DATA @ NMOT		ECO-355M-72DG	ECO-360M-72DG	ECO-365M-72DG	ECO-370M-72DG
Peak Power(Pmax)	(W)	264	268	272	276
MPP Voltage (Vmp)	(V)	36.70	36.90	37.20	37.40
MPP Current(Imp)	(A)	7.19	7.26	7.31	7.38
Open Circuit Voltage (Voc)	(V)	44.10	44.30	44.60	44.80
Short Circuit Current(Isc)	(A)	7.68	7.75	7.80	7.88

*Under Nominal Module Operating Temperature (NMOT), Irradiance of 800W/ m², Spectrum AM 1.5, Ambient Temperature 20°C, Wind Speed 1m/s

Current-Voltage Curve under different working temperatures



TEMPERATURE CHARACTERISTICS

Temperature coefficient of Pmax		-0.38%
Temperature coefficient of Voc		-0.31%
Temperature coefficient of Isc		0.05%
NMOT		41±3°C

MECHANICAL DATA


Cell Type		Mono-Crystalline, 156.75*156.75mm
Cell Arrangement		72pcs
Dimension (L*W*H)		1984*994*30mm,(1978*989*20),(1978*988*6.2)
Weight		29.4kg,27.3kg,27kg
Front Cover		2.5mm Tempered Glass
Frame		Anodized Aluminium Alloy
Junction Box		IP67, 3 Bypass Diodes
Cable Type		4mm ²
Length of Cable		240mm
Connector		PV Connector

OPTIONAL

Frame		<input type="checkbox"/> Customized
Backsheet		<input type="checkbox"/> White Glass <input type="checkbox"/> Transparent Glass
Connector		<input type="checkbox"/> Original MC4
Cable		<input type="checkbox"/> Customized
Module Size		<input type="checkbox"/> Customized

PACKING MANNER

Packing Type		40'HQ
Piece/Pallet		35
Piece/Container		770



*The specification and key features described in this datasheet may deviate slightly and are not guaranteed. Due to ongoing innovation, R&D enhancement, ECO DELTA POWER CO., LTD Reserves the right to make any adjustment to the information described herein at any time without notice. Please always obtain the most recent version of the datasheet which shall be duly incorporated into the binding contract made by the parties governing all transactions related to the purchase and sale of the products described herein.