

For a Free Quote:

Web: EnergyPal.com/solar

Call: 1-800-990-3725

Email: contact@energypal.com

EnergyPal

Solar Panel Guide Specification Data Sheet

**Eyongpv Ltd.
120W Portable solar charger
EYB120-20SPA**

Also available on the web at
EnergyPal.com/eyongpv-ltd-solar-panels/eyb120-20spa



Portable Solar

Create value for partners!

Tel.:+86-755-29420722

WeChat: 15024003838

andy@eyongpv.com <http://www.eyongpv.com>

120W Foldable solar charger

High efficiency SunPower 120W ,fabric folding solar panel

We can do different plug according to customer requested

Light weight, portable to take out.

Model No : EYP120F-20SPA

Product specification

| | |
|---------------|-------------------------------|
| Bag material | 600D |
| Bag color | Camouflage color or OEM color |
| Open size | 1750*300mm |
| Folding size | 400*300mm |
| Folding types | 1*6 |
| Net weight | 2.5 KGS |

Solar panel

| | |
|----------------------------|--|
| Solar Cell | Sunpower |
| Efficiency rate | 22.6% |
| Each Solar panel size | 272*400*3mm |
| Total solar panel qty | 6 PCS |
| Maximum power(Pm) | 120W |
| Power Tolerance | -5% |
| Voltage at max power(Vmp) | 20V |
| Current at max power(Imp) | 6A |
| Open circuit voltage(Voc) | 24V |
| Short circuit current(Isc) | 6.6A |
| Operating Temperature | - 20°C — +60°C |
| Maximum System Voltage | 700V |
| Maximum Series Fuse Rating | 8A |
| Certifications | CE、FCC、ROHS |
| Standard Test Condtion | Irrandiance 1000W/m ² , Module temperature 25°C,AM=1.5 |

Guarantee product material and process in a year

Temperature Characteristics

| | |
|----------------------------------|--------------|
| Noct :46°C ± 2°C | |
| Temperature Coefficient of Pmax: | (-0.38% /°C) |
| Temperature Coefficient of Voc: | (-0.28% /°C) |
| Temperature Coefficient of Isc: | (0.06% /°C) |

Product photo

