

For a Free Quote:

Web: EnergyPal.com/solar

Call: 1-800-990-3725

Email: contact@energypal.com

EnergyPal

Solar Panel Guide Specification Data Sheet




Tamrons Active International Limited

FSM170~190




FSM185M636

Also available on the web at

EnergyPal.com/tamrons-active-international-limited-solar-panels/fsm185m636



MANAGEMENT SYSTEM

-  ISO 9001: Quality management system
-  ISO 14001: Standard for environmental management system
-  OHSAS 18001: International standard for occupational health and safety assessment system



*BLACK FRAME/BLACK BACK-SHEET PRODUCTS ARE AVAILABLE UPON REQUEST

PRODUCT CERTIFICATES



Electrical Characteristics under STC*

Module Type	FSM170M636	FSM175M636	FSM180M636	FSM185M636	FSM190M636
Maximum Power-Pmax (Wp)	170	175	180	185	190
Voltage at Maximum Power-Vmp (V)	19.2	19.3	19.5	19.7	19.9
Current at Maximum Power-Imp (A)	8.86	9.07	9.24	9.39	9.55
Open Circuit Voltage-Voc (V)	23.4	23.6	23.9	24.1	24.4
Short Circuit Voltage-Isc (A)	9.38	9.61	9.81	9.93	10.08
Module Efficiency- η_m (%)	17.2	17.7	18.2	18.7	19.2
Power Tolerance (%)	0/+3	0/+3	0/+3	0/+3	±3

*STC (Standard Testing Conditions): Irradiance 1000W/m², cell temperature 25°C, AM=1.5

*NOCT (Nominal Operating Cell Temperature): Irradiance 800W/m², ambient temperature 20 °C, wind speed 1 m/s

Mechanical Characteristics

Cell Type	Mono-crystalline 156.75×156.75mm
Number of Cells	36 (4×9)
Dimension	1488×664×30mm
Weight	12 kg

Temperature Characteristics

NOCT*	45±2°C
Temperature Coefficient of Pmax (%)	-0.40/°C
Temperature Coefficient of Voc (%)	-0.31/°C
Temperature Coefficient of Isc (%)	0.04/°C

Maximum System Ratings

Operating Temperature	-40°C to +85°C
Maximum System Voltage	1000V DC
Maximum Series Fuse Rating	16A

Packing Configuration

Quantity per Carton	35 pieces
Quantity per 20' Container	490 pieces
Quantity per 40' Container	1,470 pieces

* The datasheet is for informational purposes only and subject to change without prior notice. Copyright © 2018 TAMRONS All rights reserved.



Positive Power Tolerance +0 ~ +4.99 w



Withstand Heavy Loading
Front load 5400 Pa & Rear Load 2400 Pa



Excellent Low Light Performance
3.5% relative eff. reduction at low-irradiance (200w/m²)



Tamrons Active International Limited

web: www.tamrons.com; mail: sales@tamrons.com

Production plants in China, Taiwan, Dubai and Thailand

can meet the customer's needs and brand OEM

