

For a Free Quote:

Web: EnergyPal.com/solar

Call: 1-800-990-3725

Email: contact@energypal.com

EnergyPal

Solar Panel Guide Specification Data Sheet

FuturaSun srl

FU240-250P

FU 245 P

Also available on the web at
EnergyPal.com/futurasun-srl-solar-panels/fu-245-p




NEW
5 BUSBAR

FU 240 / 245 / 250 P

Polycrystalline Photovoltaic Module - 54 Cells

Engineered
in Italy



Note: dimensions in mm
tolerance +/- 2 mm

GENERAL FEATURES

- **15-year product warranty**
- **High-efficiency cells** decrease ohmic losses and increase the yield
- **Tempered 3.2 mm safety glass** for optimal mechanical stability and transparency
- **High temperature resistance** (tested at 105° C for 200 hours)
- For installations **up to an altitude of 7000 m**
- Maximum **resistance against hail** (83 km/h)
- Quality control with **electroluminescence (EL) tests** on each module

CERTIFICATIONS

- > **IEC 61215:2016 - IEC 61730:2016 & Factory Inspection**
- > **Fire Resistance - Class 1**
- > **Salt Corrosion Resistance** IEC 61701
- > **Ammonia Corrosion** IEC 62716
- > **PID Test - Class A** Potential Induced Degradation
- > **Dust and Sand Resistance** IEC 60068-2-68

NEW

GUARANTEES

Performance guarantee

Max power decrease **0.5%/year**

97% at the end of first year


90% at the end of 20th year

87% at the end of **25th year**

Product guarantee

15 YEARS

- Market standard performances
- FuturaSun performances



NEW

NEW

ELECTRICAL DATA

MODULE		FU 240 P	FU 245 P	FU 250 P
<i>Standard Test Conditions STC: 1000 W/sqm - AM 1.5 - 25 °C - tolerance: Pmax (±3%), Voc (±4%), Isc (±5%)</i>				
Module power (Pmax)	W	240	245	250
Open circuit voltage (Voc)	V	34.09	34.40	35.17
Short circuit current (Isc)	A	9.03	9.11	9.17
Maximum power voltage (Vmpp)	V	27.78	28.11	28.49
Maximum power current (Impp)	A	8.65	8.73	8.80
Module efficiency	%	16.3	16.6	16.9

<i>Nominal Module Operating Temperature NMOT: 800 W/mq - T=45 °C - AM 1.5</i>				
Module power (Pmax)	W	175.63	179.29	182.95
Open circuit voltage (Voc)	V	31.30	31.58	32.29
Short circuit current (Isc)	A	7.42	7.48	7.53
Maximum power voltage (Vmpp)	V	25.16	25.46	25.80
Maximum power current (Impp)	A	6.99	7.05	7.11

TEMPERATURE RATINGS

Temperature coefficient Isc	%/°C	0.0474
Temperature coefficient Voc	%/°C	-0.285
Temperature coefficient Pmax	%/°C	-0.37
NMOT *	°C	45
Operating temperature	°C	from -40 to +85

* Nominal Module Operating Temperature

MECHANICAL SPECIFICATIONS

Dimensions	1490 x 990 x 35 mm
Weight	16.5 kg
Glass	Tempered, transparent, 3.2 mm
Cell encapsulation	EVA (Ethylene Vinyl Acetate)
Cells	54 polycrystalline cells 156.75x156.75 mm
Backsheet	Composite multilayer film
Frame	Anodized aluminium frame with mounting and drainage holes
Junction box	Certified according to IEC 62790, IP 68 approved
Cables	Solar cable, length 900 mm assembled with MC4-combinable plugs
Maximum reverse current (Ir)	20 A
Maximum system voltage	1000 V (1500 V on request)
Maximum load (wind/snow)	5400 Pa (including safety factor 1.5)
Protection Class	II - accordance to IEC 61730

Authorized Dealer



FuturaSun srl

Riva del Pasubio, 14 - 35013 Cittadella - Italy
Tel + 39 049 5979802 Fax + 39 049 0963081
www.futurasun.com - info@futurasun.it

2019_54p_240-250_en