

**For a Free Quote:**

**Web: [EnergyPal.com/solar](http://EnergyPal.com/solar)**

**Call: 1-800-990-3725**

**Email: [contact@energypal.com](mailto:contact@energypal.com)**

# **EnergyPal**

## **Solar Panel Guide Specification Data Sheet**

**FuturaSun srl**

**FU340-380M**

**FU 370 M**

Also available on the web at  
[EnergyPal.com/futurasun-srl-solar-panels/fu-370-m](http://EnergyPal.com/futurasun-srl-solar-panels/fu-370-m)




Engineered  
in Italy

**NEW**  
**5 BUSBAR**

## FU 340 / 350 / 360 / 370 / 375 / 380 M

Monocrystalline Photovoltaic Module - 72 Cells



Note: dimensions in mm  
tolerance +/- 2 mm

### GENERAL FEATURES

- **15-year product warranty**
- **High-efficiency cells** decrease ohmic losses and increase the yield
- **Tempered 3.2 mm safety glass** for optimal mechanical stability and transparency
- **High temperature resistance** (tested at 105° C for 200 hours)
- For installations **up to an altitude of 7000 m**
- Maximum **resistance against hail** (83 km/h)
- Quality control with **electroluminescence (EL) tests** on each module

### CERTIFICATIONS

- > **IEC 61215:2016 - IEC 61730:2016 & Factory Inspection**
- > **Fire Resistance - Class 1**
- > **Salt Corrosion Resistance** IEC 61701
- > **Ammonia Corrosion** IEC 62716
- > **Dust and Sand Resistance** IEC 60068-2-68

**NEW**

### GUARANTEES


#### Performance guarantee

Max power decrease **0.5%/year**  
97% at the end of first year  
**90% at the end of 20<sup>th</sup> year**  
87% at the end of **25<sup>th</sup> year**

#### Product guarantee

**15 YEARS**

■ Market standard performances  
■ FuturaSun performances



**NEW**

**NEW**

## ELECTRICAL DATA

MODULE		FU 340 M	FU 350 M	FU 360 M	FU 370 M	FU 375 M	FU 380 M*
<i>Standard Test Conditions STC: 1000 W/sqm - AM 1.5 - 25 °C - tolerance: Pmax (±3%), Voc (±4%), Isc (±5%)</i>							
Module power (Pmax)	W	340	350	360	370	375	380
Open circuit voltage (Voc)	V	46.97	47.65	48.34	48.96	49.26	49.38
Short circuit current (Isc)	A	9.07	9.2	9.41	9.66	9.81	9.91
Maximum power voltage (Vmpp)	V	38.73	39.3	39.86	40.33	40.55	40.82
Maximum power current (Impp)	A	8.78	8.91	9.04	9.18	9.25	9.31
Module efficiency	%	17.54	18.06	18.58	19.09	19.35	19.61

<i>Nominal Module Operating Temperature NMOT: 800 W/mq - T=45 °C - AM 1.5</i>							
Module power (Pmax)	W	249.74	257.08	264.4	271.8	275.4	279.1
Open circuit voltage (Voc)	V	43.32	43.95	44.59	45.16	45.43	45.55
Short circuit current (Isc)	A	7.46	7.56	7.74	7.94	8.07	8.15
Maximum power voltage (Vmpp)	V	35.05	35.57	36.07	36.5	36.7	36.94
Maximum power current (Impp)	A	7.12	7.23	7.33	7.45	7.5	7.55

## TEMPERATURE RATINGS

Short circuit voltage (Isc)	%/°C	0.0344
Open circuit voltage (Voc)	%/°C	-0.273
Module power (Pmax)	%/°C	-0.389
NMOT **	°C	45
Operating temprature	°C	from -40 to +85

\* Certification on going

\*\* Nominal Module Operating Temperature

## MECHANICAL SPECIFICATIONS

Dimensions	1957 x 990 x 40 mm
Weight	22.5 kg
Glass	Tempered, transparent, 3.2 mm
Cell encapsulation	EVA (Ethylene Vinyl Acetate)
Cells	72 monocrystalline cells 156.75x156.75 mm
Backsheet	Composite multilayer film
Frame	Anodized aluminium frame with mounting and drainage holes
Junction box	Certified according to IEC 62790, IP 68 approved
Cables	Solar cable, length 900 mm (1500 mm upon request) assembled with MC4-combinable plugs
Maximum reverse current (Ir)	20 A
Maximum system voltage	1000 V (1500 V on request)
Maximum load (wind/snow)	5400 Pa (including safety factor 1.5)
Protection Class	II - accordance to IEC 61730

Authorized Dealer



**FuturaSun srl**

Riva del Pasubio, 14 - 35013 Cittadella - Italy  
Tel + 39 049 5979802 Fax + 39 049 0963081  
www.futurasun.com - info@futurasun.it