

For a Free Quote:

Web: EnergyPal.com/solar

Call: 1-800-990-3725

Email: contact@energypal.com

EnergyPal

Solar Panel Guide Specification Data Sheet

**Shenzhen Juguangneng Science & Technology Co.,
Ltd.**

JGN-200P-72

JGN-200P-72

Also available on the web at
EnergyPal.com/shenzhen-juguangneng-science-technology-co-ltd-solar-panels/jgn-200p-72

Shenzhen JuGuangNeng Science and Technology Co., Ltd.

深圳市聚光能科技有限公司

Add: 6/F, Building A, Shuangjinhui industrial park, Fuyong, Bao'an, Shenzhen, Guangdong, China 518103

Tel: +86-755-29919483 29919542

Fax: +86-755-29923175 29923173

Website: www.chinajgn.com

E-mail: chinajgn@chinajgn.com

200W/36V Polycrystalline silicon solar module specifications

Module number	JGN-200P-72
Peak power / Pm(W)	200±3%
Open circuit voltage / Voc(V)	43.2
Max. power voltage / Vmp(V)	36.0
Max. power current / Imp(A)	5.56
Short circuit current / Isc(A)	6.22
Solar cells origin	Taiwan
Solar cells efficiency	around 17.5%
Grade of solar cells	A grade
Dimensions(L*W*T) / Weight(kgs)	1485*986*40mm/15kgs
Solar cell / No. of cells and connections	polycrystalline silicon / 72-cell in series
Front cover(material/thickness)	Low-iron tempered glass / 3.2mm
Encapsulation(material)	Ethylene Vinyl Acetate(EVA)
Frame(material/color)	Anodized aluminium alloy / Silver
Junction box protection degree	≥IP65
Cable /Cable connector Model	900mm solar cable with MC4 connectors
Standard Testing Conditions	Irradiance:1000W/m2, Cell temperature:25℃, AM:1.5(air mass).
Max. static load, front(e. g.: snow/wind)	5400Pa
Max. static load, back(e. g.: wind)	2400Pa
Max. hailstone impact (diameter/velocity)	25mm; 23m/s
Max. series fuse rating (A)	15A
Max. system voltage (V)	1000V DC
Application Class	Class A
NOCT	45±2℃
Operating temperature range	-40℃- +85℃
Power temperature coefficient	-0.45%/℃
Current temperature coefficient	0.08%/℃
Voltage temperature coefficient	-0.37%/℃
Lifespan	≥25 years
Warranty	Power output warranty: 10 years over 90%, 25 years over 80%;
Product Certifications / Standards	CE, IEC61215
Other Certifications	ISO9001:2008, RoHS

