

For a Free Quote:

Web: EnergyPal.com/solar

Call: 1-800-990-3725

Email: contact@energypal.com

EnergyPal

Solar Panel Guide Specification Data Sheet

ACS Energy Systems LEXRON36 25-190W Mono LXR70M

Also available on the web at
EnergyPal.com/acs-energy-systems-solar-panels/lxr70m

LEXRON36

25/45/70/95/120/145/185/190M

LEXRON

Renewable Energy Systems

LEXRON Solar Modules

Features



Guaranteed 0- +5W positive power output tolerance ensures high reliability



Anti-reflective, hydrophobic coating improves light absorption and reduces surface dust



Excellent performance under low light environments (mornings, evenings and cloudy days)



Entire module certified to withstand high wind loads (2400 Pascal) and snow loads (5400 Pascal)*



PEAK POWER	OPEN CIRCUIT VOLTAGE Voc(V)	SHORT CIRCUIT CURRENT Isc(A)	PEAK VOLTAGE Vmp(V)	PEAK CURRENT IMP (A)	SIZE (mm)	CELL NUMBER (pcs)	NET WEIGHT (kg)
LXR25M	22,10	1,49	18,00	1,39	430*360*25	36	1,68
LXR45M	22,10	2,78	18,00	2,50	430*670*25	36	3,8
LXR70M	22,10	4,20	18,00	3,89	600*670*25	36	5,2
LXR95M	22,10	5,45	18,80	5,05	800*670*25	36	7,0
LXR120M	22,10	7,30	18,80	6,38	970*670*30	36	8,5
LXR145M	22,60	7,90	19,00	7,63	1150*670*30	36	9,5
LXR185M	22,80	10,20	19,00	9,73	1480*670*30	36	11,9
LXR190M	22,80	10,30	19,40	9,79	1480*670*30	36	11,9

Industry-leading warranty

- 25 year transferable power output warranty: 10year/90%; 25year/80%.
- Based on nominal power.
- 10 year material and workmanship warranty.

LEXRON® is registered trade mark of ACS Energy and Technology LTD STI

Add : 1376 Sok. Boran Plaza No:3/AG Halkapınar, Izmir/Turkey

Tel: +90 232 458 0045

E-mail: info@acsenerji.com

www.acsenerji.com