

**For a Free Quote:**

**Web: [EnergyPal.com/solar](http://EnergyPal.com/solar)**

**Call: 1-800-990-3725**

**Email: [contact@energypal.com](mailto:contact@energypal.com)**

# **EnergyPal**

## **Solar Panel Guide Specification Data Sheet**

**Malaysian Solar Resources Sdn Bhd**

**MYS-60P/B3/CF-235-245**

**MYS-60P/B3/CF-240**

Also available on the web at

[EnergyPal.com/malaysian-solar-resources-sdn-bhd-solar-panels/mys-60p-b3-cf-240](http://EnergyPal.com/malaysian-solar-resources-sdn-bhd-solar-panels/mys-60p-b3-cf-240)



## Multi-Crystalline Photovoltaic Module High efficiency based on leading innovative photovoltaic technologies

**MYS-60P/B3/CF-245**

**MYS-60P/B3/CF-240**

**MYS-60P/B3/CF-235**

### High Quality of Pv Module

The MYS-60P/B3/CF-245, MYS-60P/B3/CF-240 and MYS-60P/B3/CF-235 are distinguished by multi-crystalline solar cells with high efficiency up to 14.75% for high output per square meter of module area. MSR delivers modules with positive tolerance from 0 - 4.99 watt, modules of the highest quality would be able to provide with this level of reliability.

- ▶ Modules on high output quality
  - ▶ High efficiency based on leading innovative photovoltaic technologies
  - ▶ Maximum yields and longevity due to 100% hotspot prevention
  - ▶ Excellent performance due to outstanding low-light behavior
  - ▶ Withstand high wind pressure and extreme temperature variations
  - ▶ High transparent 3.2mm / 4mm low-Iron tempered glass
  - ▶ Unique technology enable no water freezing and warping do not occur
  - ▶ Aesthetic appearance
  - ▶ 25 years power output warranty (long life span)
  - ▶ PV produces energy without emissions (green house gases) and noise free
- TUV Rheiland certified modules accordance to IEC 61215 ed. 2 2005, IEC 61730, Part 1, 2004 and IEC 61701 Salt mist corrosion testing of photovoltaic (PV) modules.



## TECHNICAL DATA

### Mechanical Parameters

overall dimensions (frame)	l x w x t	1666mm x 997mm x 42mm	mm
Weight	Mass	19 +/-1 / 23 +/-1	Kg
Tested static back load (1 h)	Pressure	2'400	N/m <sup>2</sup>
Tested static front load (1 h)	Pressure	2'400	N/m <sup>2</sup>

### Components

Glass	Tempered 3.2mm / 4mm solar glass
Photovoltaic cells	60 multi-crystalline 6" silicon-cells (156mm x 156mm)
Frame	MSR Standard, Anodized Aluminium
Junction box	Tyco (3 bypass diode) (115mm x 110mm x 22.5mm)
Plug connector type / Cable length / cross section size (mm <sup>2</sup> )	MC4 (Tyco Solarlok) / 2 x 1000mm / 4mm <sup>2</sup>

### Certificates, Safety Class and Warranty

IEC 61215 ed. 2	IEC 61215 ed. 2	= Registration No. PV60033123
IEC 61730	IEC 61730	= Registration No. PV60033124
IEC 61701	IEC 61701	= Registration No. PV60037080
CE certified	CE Compliance	= SHEMA10060074501TXC
Safety class	II	
IP protection level	65	
Warranty	10 years product warranty 10 years 90% nominal performance 25 years 80% nominal performance	

### Electrical Data at Standard Testing Conditions (STC) 1

1) Irradiance 1000 W/m<sup>2</sup>, module temperature 25°C, spectrum at air-mass AM 1.5

Model	MYS-60P/B3/CF-245	MYS-60P/B3/CF-240	MYS-60P/B3/CF-235
Nominal power @ STC1 (P <sub>MAX</sub> )	245	240	235
Voltage @ maximum power point (V <sub>mpp</sub> )	30.96	30.78	30.60
Current @ maximum power point (I <sub>mpp</sub> )	7.92	7.80	7.68
Open circuit voltage (V <sub>oc</sub> )	37.26	37.08	37.02
Short circuit current (I <sub>sc</sub> )	8.345	8.288	8.222
Temperature Coefficient	-0.39%/K - P <sub>max</sub> -0.320%/K - V <sub>oc</sub> +0.050%/K - I <sub>sc</sub>		


### General Electrical Parameters

Maximum system voltage	1,000V DC
Maximum module reverse current (I <sub>R</sub> )	15A
Operating Temperature range	-40°C to +85°C
NOCT	46 +/- 2°C



## DIMENSIONS

### I-V CURVE



#### International Marketing for Sales

Tel : +1-415-992-3291

Fax : +1-415-707-2003

sales@malaysiansolar.com

#### MSR Factory

**Malaysian Solar Resources Sdn. Bhd.**

Lot 74369, Lebuhraya Tun Razak,

26300 Kuantan,

Pahang Darul Makmur,

Malaysia.

Tel : +6 (09) 5668131

Fax : +6 (09) 5491032

www.malaysiansolar.com

I-V parameters are rated at Standard Test Conditions (irradiance of 1000W/m<sup>2</sup>, AM 1.5G, cell temperature 25°C). All measurements are guaranteed at the laminate leads. NOCT is measured at 800W/m<sup>2</sup>, 20 deg. Ambient, and 1m/s windspeed. Specifications are subject to change without notice.

## Multi-Crystalline Photovoltaic Module

