

For a Free Quote:

Web: EnergyPal.com/solar

Call: 1-800-990-3725

Email: contact@energypal.com

EnergyPal

Solar Panel Guide Specification Data Sheet

Jiangsu Runda PV Co., Ltd.

RS320-335S-120

RS320S-120




Also available on the web at
EnergyPal.com/jiangsu-runda-pv-co-ltd-solar-panels/rs320s-120

RS330S-120

- RS320S-120
- RS325S-120
- RS335S-120



Jiangsu Runda PV Co., Ltd.



10 Years
Material & Craft
Quality assurance

12 Years
90% output
Power guarantee

25 Years
80% output
Power guarantee



ISO9001
ISO14001
OHSAS18001



High Module Efficiency



Mechanical Load Capability up to 8000 Pa



Salt Mist Corrosion Protect
Ammonia Resistance



Potential Induced Degradation Free

Jiangsu Runda PV Co., Ltd.

Tel: +86-0510-83801000

Fax: +86-0510-83802000

Web: www.rundapv.com

E-mail: sales@rundapv.com

Add: Yanxiang Road 108, Ehu Town, Xishan District, Wuxi City, Jiangsu Province, P.R.China



RS330S-120

- RS320S-120
- RS325S-120
- RS335S-120

Electrical Characteristics

	TYPE	RS320S-120	RS325S-120	RS330S-120	RS335S-120
STC 1000W/M ² Module Temperature 25°C A.M.1.5	POWER OUTPUT	320	325	330	335
	MAXPOWER TOLERANCE	0-5W	0-5W	0-5W	0-5W
	MODULE EFFICIENCY (%)	19.0	19.3	19.6	19.9
	VOLTAGE MPP Vmpp	33.23	33.47	33.67	33.91
	CURRENT MPP Impp (A)	9.63	9.71	9.80	9.88
	VOLTAGE OPEN CIRCUIT Voc	41.47	41.72	41.94	42.16
	SHORT CIRCUIT CURRENT Isc (A)	10.21	10.28	10.35	10.44
NOCT 800W/M ² Environment Temperature 20°C A.M.1.5	POWER OUTPUT	245.84	249.68	253.52	257.36
	VOLTAGE MPP Vmpp (V)	30.29	30.51	30.69	30.91
	CURRENT MPP Impp (A)	8.12	8.18	8.26	8.33
	VOLTAGE OPEN CIRCUIT Voc (V)	38.29	38.52	38.72	38.93
	SHORT CIRCUIT CURRENT Isc (A)	8.68	8.74	8.80	8.88
TEMPERATURE COEFFICIENTS Isc	(% / °C)		0.046		
TEMPERATURE COEFFICIENTS Voc	(% / °C)		-0.276		
TEMPERATURE COEFFICIENTS Pmpp	(% / °C)		-0.381		
NOCT (°C)			45±2°C		

Mechanical Data

DIMENSIONS OF MODULE	1678*1002*35mm
WEIGHT(Kg)	18.5
CABLE	4mm ²
GLASS	High transmission glass 3.2mm
JUNCTION BOX	IP68, 3 Bypass-Diode, 300mm in length
TYPE OF CONNECTOR	Compatible with MC 4 plug

Working Conditions


MAX SYSTEM VOLTAGE (VDC)	1500V
SERIES FUSE RATING	15A
MECHANICAL LOAD	≥5400Pa
OPERATING TEMPERATURE (°C)	-40~+85
APPLICATION CLASS	A

Packaging Configuration

Loading Capacity	360 pcs/20GP
	832 pcs/40HC

Contact Information

I-V CURVES



Jiangsu Runda PV Co.,Ltd.

Tel: +86-0510-83801000 Fax: +86-0510-83802000
 Web: www.rundapv.com E-mail: sales@rundapv.com
 Add: Yanxiang Road 108, Ehu Town, Xishan District, Wuxi City, Jiangsu Province, P.R.China

