

**For a Free Quote:**

**Web: [EnergyPal.com/solar](http://EnergyPal.com/solar)**

**Call: 1-800-990-3725**

**Email: [contact@energypal.com](mailto:contact@energypal.com)**

# **EnergyPal**

## **Solar Panel Guide Specification Data Sheet**

**Solarland USA Corporation**

**SLP060-12C**

**SLP060-12C**

Also available on the web at  
[EnergyPal.com/solarland-usa-corporation-solar-panels/slp060-12c](http://EnergyPal.com/solarland-usa-corporation-solar-panels/slp060-12c)

# SLP060-12C

## High Efficiency Multicrystalline PV Module



Certified and Listed to  
UL1703 and CUL1703 Standards

Electrical Characteristics	SLP060-12C
Product code	060011262
Maximum power (Pmax)	60W
Voltage at Pmax (Vmp)	18.64V
Current at Pmax (Imp)	3.22A
Open-circuit voltage (Voc)	22.18V
Short-circuit current (Isc)	3.42A
Temperature coefficient of Voc	-(80±10)mV/°C
Temperature coefficient of Isc	(0.065±0.015)%/°C
Temperature coefficient of power	-(0.5±0.05)%/°C
NOCT (Air 20°C; Sun 0.8kW/m² wind 1m/s)	47±2°C
Operating temperature	-40°C to 85°C
Maximum system voltage	600V DC
Power tolerance	± 5%


\*STC: Irradiance 1000W/m², AM1.5 spectrum, module temperature 25°C

\*NOCT: Nominal operating cell temperature (the data is only for reference)



### Module Diagram


Dimensions in brackets are in inches.  
Un-bracketed dimensions are in millimeters.  
Unit: mm[in.]



### Features

- Nominal 12V DC for standard output.
- Outstanding low-light performance.
- Heavy-duty anodized frames.
- High transparent low-iron, tempered glass.
- Rugged design to withstand high wind pressure, hail and snow load.
- Aesthetic appearance.

### Characteristics



SLP060-12C I-V Curves

Specifications	SLP060-12C
Cells	Polycrystalline silicon solar cell
No. of cells and connections	36(4X9)
Module dimension	654mm[25.75in.]x675mm[26.57in.]x35mm[1.38in.]
Weight	5.7kg[12.57lbs]
Packing information(Carton)	720mm[28.35in.]x700mm[27.56in.]x105mm[4.13in.](2pcs/ctn)

\*Limited warranty: 5-year limited warranty of materials and workmanship; 10-year limited warranty of 90% power output; 25-year limited warranty of 80% power output. For detail, please contact us.

\*Specifications are subject to change without notice at any time.