

For a Free Quote:

Web: EnergyPal.com/solar

Call: 1-800-990-3725

Email: contact@energypal.com

EnergyPal

Solar Panel Guide Specification Data Sheet

Sunprism Energy Technology

SP 355-380 - M72

SP 375-M72

Also available on the web at
EnergyPal.com/sunprism-energy-technology-solar-panels/sp-375-m72

SP-M72 Series

355 W – 380 W

Monocrystalline Photovoltaic Module

SUNPRISM Energy Technology is a pioneer Egyptian manufacturing company specialized in the crystalline photovoltaic (PV) solar power industry since 2005.

Our core business is the manufacturing of photovoltaic modules in a wide range of power levels for off-grid and on-grid applications up to 380 Wp.

Our acquired experience in crystalline PV module manufacturing comes from the heritage of our world-class engineers specialized in this domain since 1992.



SP-M72 Series Features

- 72 high – performance Monocrystalline PERC silicon solar cells made with an efficiency up to 21.8%.
- High durability materials
- Manufactured with compliance to German quality standards and warranted for 10 years.
- Power output guaranteed above 80% for 25 years.



SP-M72 (355 W – 380 W)


Technical Specifications SP-M72 355 360 365

Nominal Power	P_{max}	$[W_p]$	355	360	365
Module Efficiency		%	18.13	18.38	18.64
Rated current	I_{MP}	$[A]$	9.08	9.15	9.22
Rated Voltage	V_{MP}	$[V]$	39.10	39.36	39.59
Short circuit current	I_{SC}	$[A]$	9.61	9.68	9.71
Open circuit voltage	V_{OC}	$[V]$	46.36	46.72	47.09

Technical Specifications SP-M72 370 375 380

Nominal Power	P_{max}	$[W_p]$	370	375	380
Module Efficiency		%	18.89	19.15	19.40
Rated current	I_{MP}	$[A]$	9.25	9.30	9.37
Rated Voltage	V_{MP}	$[V]$	40.01	40.34	40.57
Short circuit current	I_{SC}	$[A]$	9.75	9.80	9.87
Open circuit voltage	V_{OC}	$[V]$	47.52	47.80	48.02

Electrical data under Standard Test Conditions (STC) :Irradiance 1000W/m², Cell Temperature 25 °C, AM 1.5 +/--3% power measurement tolerance



With assembly tolerance of ± 2 mm (L & W)
± 0.8 mm Thickness

Properties for System Design

Operating Temp.	$[^{\circ}C]$	-40 to 85	Nominal Operating Cell Temp.	$[^{\circ}C]$	+ 44 ± 2
Protection class		II	Temperature coefficient I_{SC}	α $[%/^{\circ}C]$	+ 0.05
Max system voltage	V_{SYS} $[V]$	1500	Temperature coefficient V_{OC}	β $[%/^{\circ}C]$	- 0.32
Max series fuse rating	I_R $[A]$	15	Temperature coefficient P_{max}	$[%/^{\circ}C]$	- 0.370

Nominal Operating Cell Temperature (NOCT) :Irradiance 800W/m², Ambient Temperature 20 °C, Wind Speed 1m/s

Mechanical Properties

Front covering	3.2mm AR tempered solar glass	Protection class	Junction box IP68 rated, 1500 VDC
Back covering	Monolayer high grade PET	Cable	4 mm ² , length 1 m with MC4 compatible
Solar cell	72 Monocrystalline 6" PERC silicon cells	Weight	21.5 kg
Dimensions	1970 x 994 x 40 mm	HL-test	5400 Pa

Packaging Configuration 25 modules per box, 22 boxes per 40' HC container /10 boxes per 20' container

Over the years SUNPRISM Energy Technology has set high benchmarks with its high quality standards. Continuous tests guarantee a consistently high level of quality. Every module undergoes visual, mechanical, and electrical inspections. Each module will be HV-tested and examined by electro luminescence. This is recognizable by means of the original SUNPRISM label, the serial number, and the SUNPRISM guarantee:

- 10 years product warranty
- 10 years linear performance warranty for a power output of 90%
- 25 years linear performance warranty for a power output of 80%
- Detailed warranty conditions and additional information can be found in our warranty terms
- Certified according to IEC 61215 and IEC 61730

* SUNPRISM reserves the right to change specifications without prior notice

