

For a Free Quote:

Web: EnergyPal.com/solar

Call: 1-800-990-3725

Email: contact@energypal.com

EnergyPal

Solar Panel Guide Specification Data Sheet

**TSEC Corporation
TS60-6M3-295-310(5BB)
TS60-6M3-310**

Also available on the web at
EnergyPal.com/tsec-corporation-solar-panels/ts60-6m3-310



V-Series Modules

5BB Monocrystalline Solar Modules

Peak Power: 295-310Wp

High Quality

- Powered by TSEC premium grade solar cells.
- The solar cell passed UL/ITRI PID test conditions (temperature 85°C, humidity 85%, -1500V, 300hrs)
- The solar module passed ITRI PID test conditions (temperature 85°C, humidity 85%, ±1000V, 300hrs)

High Reliability

- CNS 15114 mechanical load test 5400Pa
- IEC 61215:2016 mechanical load test 3600Pa (safety factor 1.5)
- Salt mist corrosion testing up to 56 days by ITRI, follow severity 6 in IEC61701(CNS 15196) standard.

Strict Quality Control

- Current sorting for hot spot protection.
- 3-stage EL tests at pre-lamination, before framing and before delivery.
- Positive tolerance 0~4.99W

Module Characteristics



Dimension	1,650 × 992 × 40 mm
Weight	18.5 Kg

Certifications


- IEC 61215:2016、IEC 61730-1:2016 & IEC 61730-2:2016
- ISO 9001:2008 Quality management system
- ISO 14001:2015 Standards for environmental management system
- ISO 50001:2011 Energy management system
- OHSAS 18001:2007 International standards for occupational health and safety

Warranty



- 10-year materials and workmanship warranty.
- 25-year linear power warranty.



Module Front Side



Module Rear Side



V-Series 310W

5BB Monocrystalline Solar Module



Make the best better.
www.tsecpv.com

Performance Under Standard Test Conditions

Model Name			TS60-6M3-295	TS60-6M3-300	TS60-6M3-305	TS60-6M3-310
Max. power at STC	P_{max}	W	295	300	305	310
Max. power voltage	V_{mp}	V	31.69	32.15	32.56	32.87
Max. power current	I_{mp}	A	9.31	9.33	9.37	9.43
Open circuit voltage	V_{oc}	V	38.87	39.25	39.50	40.25
Short circuit current	I_{sc}	A	9.92	9.94	9.95	9.97
F.F. (%)		%	76.51%	76.88%	77.63%	77.96%
Module Conversion Eff.		%	18.02%	18.33%	18.63%	18.94%
Module Effective Conversion Eff.		%	20.12%	20.46%	20.81%	21.15%

* Under Standard Test Condition (1,000W/m², 25°C, AM 1.5): Power Tolerance ±3%

* Module Conversion Eff. (%) = [Max power at STC(w) / (Solar Module Area(m²) × 1000 (w/m²))] × 100%

* Module Effective Conversion Eff. (%) = [Max power at STC(w) / (Solar Cell Total Area(m²) × 1000 (w/m²))] × 100%



Thermal Characteristics

Normal Operating cell temperature	NMOT	°C	45±2
TC I _{sc}	α _{I_{sc}}	%/°C	+0.073
TC V _{oc}	β _{V_{oc}}	%/°C	-0.33
TC P _{max}	δ	%/°C	-0.44


System Integration Parameters

Max. system voltage	1000V
Module fire resistance class	Class C
Application class (Safety class II)	Class A
series fuse rating	15 A
Number of bypass diodes	3
Temperature range	-40 to +85°C
Max. mechanical load	5400 pa(VPC) 3600 Pa (IEC 61215 : 2016)

Component Material

Cell type	Monocrystalline / 156.75 x 156.75mm
Cell per module	5BB / 60 pcs
Front	Low-iron glass / Tempered
Encapsulant Film	Ethylene Vinyl Acetate(EVA)
Rear	Backsheet
Frame	6063T5 Anodized aluminum (silver/black)
Junction Box	IP68 Type 1  Type 2 
Connector	MC4 Compatible
Cable	1000mm / 12 AWG / 4mm ²

IV Curve



TSEC Corporation

Taipei Headquarters

8F., No.225, Sec3, Beixin Rd., Xindian Dist., New Taipei City
231, Taiwan, R.O.C T +886-2-2912-2199
F +886-2-2917-5399 M taiwan.sales@tsecpv.com(EPC Business)
epc@tsecpv.com(EPC Engineering)

Hsinchu Plant

No.85, Guangfu N. Rd., Hukou Township, Hsinchu County 30351,
Taiwan, R.O.C. (Hsinchu Industrial Park)
T +886-3-696-0707 F +886-3-696-0708

Pingtung Plant

No.335-12, Daxi Rd., Pingtung City, Pingtung County 90063,
Taiwan, R.O.C.
T +886-8-753-6899 F +886-8-753-3279

Overseas Bases

TSEC America Inc.

1235 N Harbor Blvd Ste 240 Fullerton, CA 92832, U.S.A.
T 1-714-449-0966 M Occident@tsecpv.com

TSEC Thailand Office

279, Srinakarin Rd., Nong Bon, Prawet, Bangkok 10250 Thailand.
(279 ถนนศรีนครินทร์ แขวงหนองบอน เขตประเวศ กรุงเทพฯ 10250)
T +66-2747-3999 ext.313 F +66-2747-3133 M southasia@tsecpv.com

* The information in this document is subject to change without notice.
* TSEC reserves the rights of final interpretation and revision of datasheet.
Version: March 2018.