

For a Free Quote:

Web: EnergyPal.com/solar

Call: 1-800-990-3725

Email: contact@energypal.com

EnergyPal

Solar Panel Guide Specification Data Sheet

**Target Solar Company
WS360-375G6M
WS375**

Also available on the web at
EnergyPal.com/target-solar-company-solar-panels/ws375



Mono-crystalline Silicon Photovoltaic Module



WS360-375WG6M

Features :

- High power module using 6" mono-crystalline solar cell.
- Bypass diode minimizes power drop by shade.
- Using optical low iron tempered glass, EVA laminate and Tedlar backsheet.
- Anodize aluminum frame protected.
- Manufactured in ISO 9001 : 2000 certified facility.
- 20-years limited warranty on power output.

NO.7-1, Ln.3, Xinhe 1st Rd., Tainan City 702, Taiwan

TEL: +886-6-2648199 FAX: +886-6-2657069

www.target-solar.com

info@target-solar.com

Specifications :

Model \ Power	360W	365W	370W	375W
Max power voltage Vmp(V)	39.44	39.73	40.01	40.24
Max power current Imp(A)	9.13	9.19	9.25	9.32
Open circuit voltage Voc(V)	47.52	47.74	47.95	48.54
Short circuit current Isc(A)	9.84	9.93	10.02	10.03
Weight(KG)	22.5			
Number of cells	72			
Module Efficiency(%)	18.6%	18.8%	19.1%	19.35%
Power Tolerance	+/-3%			

*1 STC: Irradiance level 1000 W/m²; Spectral AM1.5; Temperature 25°C

*2 Power tolerance can be adjusted upon requests


*3 NOCT: 46±2°C

Mechanical Characteristics


Dimensions of the Module (W×H×D)(mm) 1948X995X40

Junction box IP 67 or above with 3 bypass diodes ; cables 1.3M/φ 4mm²

Series fuse rating Inside Junction Box 15A



IV Curve



Packing Configuration

Container	20'GP	40'HQ
Pieces per pallet	52	26
Pallets per container	5	24
Pieces per container	260	624

Warranty

Product Warranty:

10 Years for Material and Workmanship

Performance Guarantee:

90% for 10 Years Guaranteed Output

80% for 25 Years Guaranteed Output

Working Condition

Maximum System Voltage: 1000V

Operating Temperature: -40 ~ +85°C

Maximum Static Load: Snow load 5400pa

Wind load 3600pa

Temperature Coefficient

Isc Temperature Coefficient: α(%/°C) +0.06

Voc Temperature Coefficient: β(%/°C) -0.33

Pmax Temperature Coefficient: γ(%/°C) -0.44

NO.7-1, Ln.3, Xinha 1st Rd., Tainan City 702, Taiwan

TEL: +886-6-2648199 FAX: +886-6-2657069

www.target-solar.com

info@target-solar.com